






GASOLINE GENERATOR - 3000rpm
Technical Data-Open type

Generator		HY65CLE
Rated Power	kVA	4.5
Max. Power	kVA	5.0
Phase/Wire		1 phase / 2 wires
Voltage	V	220
Voltage fluctuation		±1%
Frequency	Hz	50
Frequency fluctuation		±5%
Display		LED5
Fuel tank capacity	L	25
Fuel Consumption	L/h	2.8
Sound level @7m	dB(A)	76
Battery Charge	V	12
Engine		LV420
Engine type		4 stroke, air-cooled gasoline, OHV type
Power	hp	13
Compression ratio		8.0:1
Bore*Stroke		90*66
Number of cylinder		1
Start		Manual/Electric
Displacement	cc	420
Oil capacity	L	1.4
Alternator		AL5
Power	kW	5
Power Factor		1
Voltage Regulator		AVR
Dimension and weight		
Net weight	kg	73
Gross weight	kg	
Machine size (L*W*H)	mm	685x512x550
Loading Capacity FCL20/40HQ	mm	96/272



Optional Accessories	Electrical and Mechanical standards	Recommended spare part
 ATS control box (50A)	1 phase (2x16A European sockets) LED 5 displays: voltage, current, frequency, power, running time Earth connection ATS connector Key electric start Intergrate steel tank coated with electrostatic paint Solid built and strong frame with anti-vibration and electrostatic coated Mechanical transmission: direct drive with a coaxial coupling	 Air filter core
 Remote controller		 Fuel filter element
 Push wheel kit		Other standards Available working conditions: <ul style="list-style-type: none"> • Climate : tropical hot • Environmental temperature: 0-40°C • Humidity: 0-85%